



Traditional
Fireplace
Design Collection



FEATURED Alpha fireplace with radiant face design and Vintage Ceramic Fiber Liner

ALPHA

The Alpha fireplace will be a showpiece in any setting. The Alpha is a full-sized fireplace system complete with zero-clearance firebox, gas log set with electronic ignition, concealed controls and remote control. Available in 32" & 36" models, the Alpha allows you to enjoy the realism of full size Boulder Mountain logs and glowing coals featuring outstanding log aesthetics. A full set of both circulating radiant face and rolled louver panels come standard with these models, as well as Vintage Ceramic Fiber Liners and a fan for greater heat distribution. Simply add a cabinet mantel or custom mantel (as shown) to complete the look.



Wood Mantels in a variety of styles and finishes



Remote Control (included with electronic model only)

ADDITIONAL OPTIONS

- Perimeter trim kits in a variety of finishes
- * Remote control systems (hand-held and wall mounted) Millivolt only
- Outside air kits





Vintage Ceramic Fiber Liner (Standard)


EXCLUSIVE FEATURES

- Available in 32" and 36" models
- Offered in both radiant (clean-face) and rolled louvered models
- Millivolt (remote ready) or electronic (remote included) ignition systems
- Concrete refractory logs with glowing center ceramic fiber log for added realism
- Blower and Vintage Ceramic Fiber Liner are standard
- Lifetime Limited Warranty

APPLIANCE SPECIFICATIONS







| | ALPHA 32 | ALPHA 36 | |
|---|----------|----------|--|
| A | 22-1/2" | 25" | |
| В | 34-1/2" | 41-1/8" | |
| C | 18" | 21" | |
| D | 29-3/8" | 35-1/16" | |
| E | 32" | 36" | |
| F | 16-3/4" | 21-3/16" | |

As with any heating appliance, fireplace or stove, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.

Local conditions, such as elevation and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling height, accessories chosen and


 $\label{eq:decomposition} Diagrams, illustrations and photographs are not to scale-consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.$

Built to ANSI Z21.11.2 standard and approved by PFS Test Laboratories. Consult your distributor for local fireplace

FRAMING SPECIFICATIONS

| | ALPHA 32 | ALPHA 36 |
|--------|----------|----------|
| WIDTH | 34-7/8" | 41-1/2" |
| HEIGHT | 36-3/4" | 40-1/2" |
| DEPTH | 16-1/4" | 20-3/4" |

CORNER FRAMING SPECIFICATIONS



| | ALPHA 32 | ALPHA 36 | |
|---|----------|----------|--|
| G | 39-3/8" | 50-3/8" | |
| Н | 27-3/4" | 35-3/8" | |
| I | 55-5/8" | 71-1/4" | |
| J | 34-1/2" | 41-1/2" | |

FIREPLACE EFFICIENCIES

| MODEL | FUEL | BTU/HR | AFUE* |
|---------------------|------|---------------|-------|
| ALPHA 32 MILLIVOLT | NG | 17,000-25,000 | 99.9% |
| ALPHA 32 MILLIVOLT | LP | 17,000-25,000 | 99.9% |
| ALPHA 36 MILLIVOLT | NG | 20,000-33,000 | 99.9% |
| ALPHA 36 MILLIVOLT | LP | 20,000-33,000 | 99.9% |
| ALPHA 32 ELECTRONIC | NG | 20,000-25,000 | 99.9% |
| ALPHA 32 ELECTRONIC | LP | 20,000-25,000 | 99.9% |
| ALPHA 36 ELECTRONIC | NG | 22,000-33,000 | 99.9% |
| ALPHA 36 ELECTRONIC | LP | 22,000-33,000 | 99.9% |
| | | | |

*Annual Fuel Utilization Efficiency (AFUE) is the recognized U.S. rating system for the total efficiency of heating products.







